



US011740051B2

(12) **United States Patent**
Williams

(10) **Patent No.:** **US 11,740,051 B2**

(45) **Date of Patent:** **Aug. 29, 2023**

(54) **FREE FLOATING HANDGUARD ANCHORING SYSTEM**

(71) Applicant: **Springfield, Inc.**, Geneseo, IL (US)

(72) Inventor: **Charles David Williams**, Geneseo, IL (US)

(73) Assignee: **Springfield, Inc.**, Geneseo, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/448,927**

(22) Filed: **Sep. 27, 2021**

(65) **Prior Publication Data**

US 2022/0260335 A1 Aug. 18, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/928,136, filed on Jul. 14, 2020, now Pat. No. 11,131,525, which is a continuation of application No. 16/517,847, filed on Jul. 22, 2019, now Pat. No. 10,712,123, which is a continuation of application No. 16/003,171, filed on Jun. 8, 2018, now Pat. No. 10,401,122.

(60) Provisional application No. 62/517,133, filed on Jun. 8, 2017.

(51) **Int. Cl.**
F41C 23/16 (2006.01)
F41G 11/00 (2006.01)

(52) **U.S. Cl.**
CPC **F41C 23/16** (2013.01); **F41G 11/003** (2013.01)

(58) **Field of Classification Search**
CPC F41C 23/16
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

282,194 A	7/1883	Howe
496,231 A	4/1893	Richard et al.
541,560 A	6/1895	Lyman
802,279 A	10/1905	Frommer
861,939 A	7/1907	Benet et al.
1,065,341 A	6/1913	Browning
1,125,937 A	1/1915	Benet et al.
1,143,170 A	6/1915	Browning
1,150,756 A	8/1915	Gocke
1,266,087 A	5/1918	Williams

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2612519 A1	12/2006
CA	2616472 A1	2/2007

(Continued)

OTHER PUBLICATIONS


US 8,561,336 B2, 10/2013, Gomez (withdrawn)
(Continued)

Primary Examiner — Gabriel J. Klein
(74) *Attorney, Agent, or Firm* — Woodard, Emhardt, Henry, Reeves & Wagner, LLP

(57) **ABSTRACT**

Handguard anchoring systems suitable for attaching a handguard to a firearm are disclosed, including systems having a fastener that extends into a barrel nut and compresses at least a portion of the handguard between the fastener and the barrel nut. Many embodiments include openings in the handguard and/or a plate that are oversized for the fastener such that the handguard may be rotated relative to the barrel nut when a portion of the fastener is positioned within the opening.

24 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

1,474,209 A	11/1923	Reynolds	7,827,722 B1	11/2010	Davies
1,517,328 A	12/1924	Weiss	7,905,041 B1	3/2011	Davies
2,364,487 A	12/1944	Swartz	D637,684 S	5/2011	Kimmel et al.
2,779,119 A	1/1957	Fawcett	7,941,959 B1	5/2011	Swan
2,902,933 A	9/1959	Moldofsky et al.	7,963,203 B1	6/2011	Davies
2,951,424 A	9/1960	Stoner	8,028,456 B2	10/2011	Peterson
3,075,314 A	1/1963	Bakker	8,028,460 B2	10/2011	Williams
3,198,076 A	8/1965	Stoner	8,037,633 B1	10/2011	Troy
3,543,429 A	12/1970	Bendele et al.	8,037,806 B2	10/2011	Davies
3,721,031 A	3/1973	Falterman et al.	8,046,949 B1	11/2011	Daniel
3,793,922 A	2/1974	Angell et al.	8,051,595 B2	11/2011	Hochstrate et al.
4,090,305 A	5/1978	Cassidy	8,069,604 B2	12/2011	LaRue
4,304,061 A	12/1981	Brouthers	8,087,194 B1	1/2012	Vuksanovich
4,742,636 A	5/1988	Swan	8,141,285 B2	3/2012	Brown
4,765,224 A	8/1988	Morris	8,141,287 B2	3/2012	Dubois
D300,161 S	3/1989	Baldus	8,141,289 B2	3/2012	Gomez et al.
4,841,657 A	6/1989	Mossberg	8,201,353 B1	6/2012	Swan
4,845,871 A	7/1989	Swan	8,205,373 B1	6/2012	Ubl et al.
5,142,806 A	9/1992	Swan	8,230,633 B1	7/2012	Sisk
5,198,600 A	3/1993	E'Nama	8,230,634 B1	7/2012	Davies et al.
5,225,615 A	7/1993	Talbot et al.	8,234,809 B2	8/2012	Daniel
5,276,988 A	1/1994	Swan	8,240,074 B2	8/2012	Vuksanovich
5,343,650 A	9/1994	Swan	8,276,303 B2	10/2012	Kapusta et al.
5,412,895 A	5/1995	Krieger	8,276,304 B2	10/2012	Samson et al.
5,533,292 A	7/1996	Swan	8,307,751 B2	11/2012	Adolphsen
RE35,381 E	11/1996	Rose	8,316,574 B1	11/2012	Swan
5,590,484 A	1/1997	Mooney et al.	8,336,243 B2	12/2012	Langevin et al.
5,595,602 A	1/1997	Harlan	8,347,540 B2	1/2013	Sirois
5,661,255 A	8/1997	Webb	8,359,779 B2	1/2013	Daniel et al.
5,729,927 A	3/1998	Shaver	8,397,416 B2	3/2013	Laney et al.
5,740,626 A	4/1998	Schuetz et al.	8,429,845 B1	4/2013	Swan
5,826,363 A	10/1998	Olson	8,448,367 B2	5/2013	Samson et al.
5,946,842 A	9/1999	Nyzell et al.	8,453,364 B2	6/2013	Kucynko
5,952,602 A	9/1999	Gussalli	8,464,457 B2	6/2013	Troy et al.
6,044,748 A	4/2000	Westrom	8,468,929 B2	6/2013	Larson et al.
6,293,040 B1	9/2001	Luth	8,528,246 B2	9/2013	Telles
6,295,751 B1	10/2001	Piwonski	8,561,335 B2	10/2013	Brown
6,321,477 B1	11/2001	Watson, Jr.	8,578,642 B2	11/2013	Troy et al.
6,345,464 B1	2/2002	Kim et al.	8,595,970 B2	12/2013	Picciotta et al.
6,418,655 B1	7/2002	Kay	8,601,734 B1	12/2013	Hopkins et al.
6,490,822 B1	12/2002	Swan	8,607,490 B1	12/2013	Zinsner
6,499,245 B1	12/2002	Swan	8,806,792 B2	1/2014	Yan et al.
6,508,027 B1	1/2003	Kim	8,640,372 B2	2/2014	Hochstrate et al.
6,606,812 B1	8/2003	Gwinn, Jr.	8,667,882 B1	3/2014	Larson et al.
6,618,976 B1	9/2003	Swan	8,667,883 B1	3/2014	Larson et al.
6,634,128 B1	10/2003	Vastag	8,689,477 B2	4/2014	Gomez et al.
6,671,990 B1	1/2004	Booth	8,689,478 B2	4/2014	Patel
6,694,660 B1	2/2004	Davies	8,707,850 B1	4/2014	Davies
6,769,209 B2	8/2004	Mendoza-Orozco	8,713,838 B2	5/2014	Ubl et al.
6,848,351 B1	2/2005	Davies	8,726,557 B2	5/2014	Stone et al.
6,854,206 B2	2/2005	Oz	8,726,558 B1	5/2014	Nason
6,860,053 B2	3/2005	Christiansen	8,726,559 B1	5/2014	Mueller
6,895,708 B2	5/2005	Kim et al.	8,739,448 B2	6/2014	Kimmel et al.
6,959,509 B2	11/2005	Vais	8,739,449 B2	6/2014	Patel
7,059,076 B2	6/2006	Stoner et al.	8,769,853 B1	7/2014	LaRue
RE39,465 E	1/2007	Swan	8,776,420 B2	7/2014	Langevin et al.
7,204,052 B2	4/2007	Swan	8,782,943 B2	7/2014	Jarboe
7,216,451 B1	5/2007	Troy	8,783,160 B2	7/2014	Hochstrate et al.
RE40,216 E	4/2008	Swan	8,806,793 B2	8/2014	Daniel et al.
7,356,962 B2	4/2008	Swan	8,819,980 B2	9/2014	Geissele
7,363,741 B2	4/2008	DeSomma et al.	8,839,545 B1	9/2014	Gangl et al.
7,458,179 B2	12/2008	Swan	8,844,186 B2	9/2014	LeClair
7,464,496 B1	12/2008	Davies et al.	RE45,185 E	10/2014	Davies
7,493,721 B2	2/2009	Swan	8,863,426 B1	10/2014	Zinsner
7,523,580 B1	4/2009	Tankersley	8,904,691 B1	12/2014	Kincel
7,584,567 B1	9/2009	DeSomma et al.	8,919,025 B2	12/2014	Kucynko
7,640,689 B2	1/2010	Fluhr	8,931,196 B1	1/2015	LaRue
7,676,975 B2	3/2010	Phillips et al.	8,985,007 B2	3/2015	Larson et al.
7,707,762 B1	5/2010	Swan	8,991,092 B2	3/2015	Shipman et al.
7,716,865 B2	5/2010	Daniel et al.	9,003,686 B2	4/2015	Brown
7,757,422 B1	7/2010	Swan	9,010,009 B2	4/2015	Buxton
7,757,423 B1	7/2010	Swan	9,032,659 B1	5/2015	Duneman
7,770,317 B1	8/2010	Tankersley	9,140,506 B2	9/2015	Gomez
7,775,150 B2	8/2010	Hochstrate et al.	9,140,520 B2	9/2015	Lopes et al.
7,793,452 B1	9/2010	Samson et al.	9,157,697 B2	10/2015	LeClair
			9,200,867 B1	12/2015	Swan
			9,212,865 B2	12/2015	Dubreuil
			9,228,799 B2	1/2016	Kucynko
			9,234,717 B2	1/2016	Jarboe

(56)

References Cited

U.S. PATENT DOCUMENTS

9,279,632 B2 3/2016 Hochstrate et al.
 9,279,638 B2 3/2016 Adair et al.
 9,279,639 B2 3/2016 Hines
 9,297,609 B2 3/2016 Burt
 9,303,949 B1 4/2016 Oglesby
 9,322,609 B2 4/2016 Davies
 9,335,117 B2 5/2016 Miller et al.
 9,389,043 B1 7/2016 Zhang
 9,453,694 B1 9/2016 Storch
 9,464,864 B2 10/2016 Merlino et al.
 9,464,865 B2 10/2016 Shea et al.
 9,476,672 B2 10/2016 Wells et al.
 9,528,793 B1 12/2016 Oglesby
 9,557,137 B2 1/2017 Dzwil
 9,964,380 B1 5/2018 Oglesby
 10,145,648 B1 12/2018 Holder et al.
 10,345,074 B1 7/2019 Zamlinskiy
 10,532,447 B2 1/2020 Hamby
 2002/0116857 A1 8/2002 Wonisch et al.
 2006/0162217 A1 7/2006 Longueira
 2006/0260169 A1 11/2006 Samson et al.
 2007/0017139 A1 1/2007 LaRue
 2007/0033851 A1 2/2007 Hochstrate et al.
 2007/0199435 A1 8/2007 Hochstrate et al.
 2007/0261285 A1 11/2007 Troy
 2008/0092422 A1 4/2008 Daniel et al.
 2009/0013579 A1 1/2009 Fluhr
 2009/0044439 A1 2/2009 Phillips et al.
 2010/0095575 A1 4/2010 Swan
 2010/0126054 A1 5/2010 Daniel et al.
 2010/0175293 A1 7/2010 Hines
 2010/0212201 A1 8/2010 Kincel et al.
 2010/0269392 A1 10/2010 Swan
 2010/0282066 A1 11/2010 Tankersley
 2010/0287809 A1 11/2010 Williams
 2010/0300277 A1 12/2010 Hochstrate et al.
 2010/0319231 A1 12/2010 Stone et al.
 2011/0000119 A1 1/2011 Desomma et al.
 2011/0016762 A1 1/2011 Davies
 2011/0061281 A1 3/2011 Kapusta et al.
 2011/0099869 A1 5/2011 Bentley
 2011/0119981 A1 5/2011 LaRue
 2011/0126443 A1 6/2011 Sirois
 2011/0167701 A1 7/2011 Williams
 2011/0192066 A1 8/2011 Kimmel et al.
 2011/0214327 A1 9/2011 DeSomma
 2011/0239513 A1 10/2011 Sandman
 2011/0247254 A1 10/2011 Barnes
 2011/0252625 A1 10/2011 Daniel
 2011/0303082 A1 12/2011 Hochstrate et al.
 2012/0005936 A1 1/2012 Daniel
 2012/0036756 A1 2/2012 Brown
 2012/0042557 A1 2/2012 Gomez et al.
 2012/0073177 A1 3/2012 Laney et al.
 2012/0096755 A1 4/2012 Griffin
 2012/0117845 A1 5/2012 DeSomma
 2012/0124880 A1 5/2012 LeClair
 2012/0131834 A1 5/2012 Barrett et al.
 2012/0131835 A1 5/2012 Barrett et al.
 2012/0132068 A1 5/2012 Kucynko et al.
 2012/0137563 A1 6/2012 Ubl et al.
 2012/0180358 A1 7/2012 Samson et al.
 2012/0186123 A1 7/2012 Troy et al.
 2012/0216439 A1 8/2012 Barrett et al.
 2012/0285317 A1 11/2012 Davies
 2012/0291329 A1 11/2012 Ubl et al.
 2012/0317859 A1 12/2012 Brown
 2012/0324775 A1 12/2012 Troy et al.
 2013/0019513 A1 1/2013 Telles
 2013/0047832 A1 2/2013 Hochstrate et al.
 2013/0055613 A1 3/2013 Gomez et al.
 2013/0097910 A1 4/2013 Daniel et al.
 2013/0180151 A1 7/2013 Moore
 2013/0205637 A1 8/2013 Patel
 2013/0263732 A1 10/2013 Kucynko

2014/0000142 A1 1/2014 Patel
 2014/0026459 A1 1/2014 Yan et al.
 2014/0033588 A1 2/2014 Laney et al.
 2014/0033590 A1 2/2014 Gomez
 2014/0068987 A1 3/2014 Burt
 2014/0075817 A1 3/2014 Gomez
 2014/0076146 A1 3/2014 Gomez
 2014/0076147 A1 3/2014 LaRue
 2014/0076148 A1 3/2014 LaRue
 2014/0076152 A1 3/2014 Hochstrate et al.
 2014/0115938 A1 5/2014 Jarboe
 2014/0130390 A1 5/2014 Giessel
 2014/0144059 A1 5/2014 Giessel
 2014/0345179 A1 11/2014 Adair et al.
 2014/0373419 A1 12/2014 LeClair
 2015/0007477 A1 1/2015 Langevin et al.
 2015/0007478 A1 1/2015 Barrett et al.
 2015/0007712 A1 1/2015 Larson et al.
 2015/0135572 A1 5/2015 Davies
 2015/0135576 A1 5/2015 Wells et al.
 2015/0143730 A1 5/2015 Laney et al.
 2015/0168092 A1 6/2015 Stone
 2015/0168095 A1 6/2015 Dubreuil
 2015/0168096 A1 6/2015 Miller et al.
 2015/0241166 A1 8/2015 Hines
 2015/0247695 A1 9/2015 Jarboe
 2015/0247699 A1 9/2015 Davies
 2015/0247700 A1 9/2015 Merlino et al.
 2015/0316347 A1 11/2015 Shea et al.
 2015/0369555 A1 12/2015 Daniel et al.
 2016/0010946 A1 1/2016 Gibbens et al.
 2016/0033225 A1 2/2016 Selvetti
 2016/0054096 A1 2/2016 Dzwil
 2016/0084596 A1 3/2016 Gomez
 2016/0091276 A1 3/2016 Miller et al.
 2016/0131447 A1 5/2016 Hochstrate et al.
 2016/0153744 A1 6/2016 Teetzel et al.
 2016/0169617 A1 6/2016 Daley, Jr.
 2016/0178316 A1 6/2016 Miller et al.
 2016/0195360 A1 7/2016 Davies
 2016/0209166 A1 7/2016 Larson, Jr. et al.
 2016/0282069 A1 9/2016 Storch
 2016/0282083 A1 9/2016 Storch
 2016/0290761 A1 10/2016 Cook, Jr. et al.
 2017/0059273 A1 3/2017 Geissele
 2017/0160048 A1 6/2017 Galletta, II
 2018/0180370 A1 6/2018 Zheng
 2018/0306551 A1* 10/2018 Reid F41A 21/485
 2018/0356181 A1 12/2018 Williams
 2020/0240737 A1 7/2020 Wheeler et al.

FOREIGN PATENT DOCUMENTS

CA 2625261 A1 5/2007
 CA 2765149 A1 12/2010
 CA 2889273 A1 5/2014
 CA 2877197 A1 7/2015
 CZ 303 588 B6 12/2012
 DE 10 2010 023 466 A1 12/2011
 DE 10 2013 008 241 A1 11/2014
 DE 10 2013 208 770 A1 11/2014
 EP 1 998 134 A2 12/2008
 EP 1 949 014 B1 1/2010
 EP 2 141 441 A2 1/2010
 EP 2 191 224 A2 6/2010
 EP 2 634 522 A1 9/2013
 EP 2 446 214 B1 1/2014
 EP 2 894 431 A1 7/2015
 EP 2 896 927 A1 7/2015
 GB 891448 3/1962
 KR 10-2008-0034451 4/2008
 KR 10-2008-0034454 4/2008
 KR 10-2008-0036988 4/2008
 KR 10-2008-0067345 7/2008
 KR 10-2013-0076902 7/2013
 KR 1358970 1/2014
 KR 10-2014-0056391 5/2014
 KR 1564570 10/2015
 WO WO 2005/047801 A3 5/2005

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 2006/103062	A1	10/2006
WO	WO 2006/103062		10/2006
WO	WO 2006/138106	A3	12/2006
WO	WO 2008/060310	A3	5/2008
WO	WO 2008/103193	A3	8/2008
WO	WO 2009/082520	A3	7/2009
WO	WO 2009/131721	A3	10/2009
WO	WO 2010/0151552		12/2010
WO	WO 2013/010515	A1	1/2013
WO	WO 2014/031593	A3	2/2014
WO	WO 2014/066759	A1	5/2014
WO	WO 2016/028908	A1	2/2016
WO	WO 2016/089863	A3	6/2016

OTHER PUBLICATIONS

Abstract, Bibliographic Data for WO 2009/082520 corresponding to EP2191224.
 Aero Precision, MrE1 Handguard Barrel Nut and AR15 Bar Barrel Nut, <https://aeroprecisionusa.com/catalogsearch/result/?q=M5E1+Handguard+Barrel+Nut>.
 Daniel Defense Bolt-Up Plate, <https://danieldefense.com/catalogsearch/result/?q=bolt-up+plate>.
 English Machine Translation of KR1358970 obtained from Pat Base on Oct. 14, 2019.

English Machine Translation of KR1564570 obtained from Pat Base on Oct. 14, 2019.
 English Translation of CZ303588 obtained from Lexis-Nexis Total Patent on Oct. 14, 2019.
 English Translation of DE 10 2010 023 466 A1. Translation obtained from Lexis-Nexis Total Patent on Oct. 14, 2019.
 English Translation of DE 10 2013 008 241 A1. Translation obtained from Lexis-Nexis Total Patent on Jun. 27, 2017.
 English Translation of DE 10 2013 208 770 A1. Translation obtained from Lexis-Nexis Total Patent on Oct. 14, 2019.
 English Translation of DE102005054917 obtained from Lexis-Nexis Oct. 14, 2019.
 English Translation of KR 10-2008-0036988 obtained from Lexis-Nexis PatBase on Oct. 14, 2019.
 English Translation of KR20130076902, Retrieved from PatBase on Oct. 14, 2019.
 Noveske NSR Barrel Nut, Noveske Rifleworks, L.L.C., <https://www.noveske.com/search?type=product&q=NSR>.
 Parallax Tactical, FFSSR Rail System, <https://parallaxtactical.com/search?q=FFSSR>.
 Seekins Precision Rail Mountain System in which a rail is attached using screws, <http://www.seekinsprecision.com/parts-and-accessories/handguards.html>.
 US 2010/319231 corresponding to EP2446214.
 Wilson Combat, Tactical Rail Interface (T.R.I.M.), <http://shopwilsoncombat.com/TRIM-Tactical-Rail-Interface-Modular-126/productinfo/TR-TRIM-12/>.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16

FREE FLOATING HANDGUARD ANCHORING SYSTEM

BACKGROUND

The present disclosure pertains generally to firearms of various actions (e.g., bolt-action, lever-action, and semi-automatic action), including, but not limited to, modern sporting rifles like the AR-15 and M-16 style weapons. Specifically, the present disclosure pertains to systems for attaching a handguard to a firearm. Handguard anchoring systems currently exist; however, there continues to be a desire and need for new designs.

SUMMARY

The present disclosure pertains generally to systems for anchoring a handguard to a firearm. In certain aspects, the systems disclosed herein include a fastener extending through the handguard and into the barrel nut. In some instances, disclosed systems comprise a barrel nut having a circumference with a plurality of openings positioned therearound; a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm; and a plate defining a plate opening arranged to receive a fastener; wherein when mounted on the firearm, the sidewall of the handguard is captured between the plate and the barrel nut and the fastener has portions positioned in the plate opening, the side opening, and the first opening of the barrel nut.

Arrangements of the disclosed systems can have a width of a portion of the fastener received within the side opening of the handguard that is at least 10% smaller, at least 20% smaller, or at least 50% smaller than a corresponding width of the side opening of the handguard so as to allow movement of the fastener from a first portion of the side opening into a second portion of the side opening as the handguard rotates about an axis of the barrel nut. In some instances, the fastener is sufficiently smaller than the side opening so as to allow rotational movement of the handguard about the barrel nut at least about the width of the fastener, before the fastener is tightly fastened for use.

The present disclosure also provides the plate can have a first portion and a second portion, the first portion smaller than and receivable within the side opening and a second portion larger than the side opening and positionable on an exterior surface of the handguard; wherein the side opening of the handguard has a length and a width; wherein the first portion of the plate has a length and a width; and/or wherein the first portion is sufficiently smaller than the side opening of the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening when positioned therein.

The plates of the present disclosure can include a first portion having a width that is at least 10% smaller, at least 20% smaller, or at least 50% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening as the handguard rotates about an axis of the barrel nut.

In the disclosed embodiments, the length of the side opening can be greater than the width of the side opening. Additionally or alternatively, the length of the first portion of the plate can be greater than the width of the second portion of the plate so as to allow longitudinal movement of the plate

relative to the handguard when the fasteners are loose. Embodiments may also have the length of the second portion of the plate being greater than the width of the second portion of the plate. In some instances the ratio of length:width of the first portion of the plate is greater than a ratio of length:width of the side opening.

In the disclosed embodiments, the barrel nut can have a longitudinal axis along which a barrel of the firearm is received and each opening of the plurality of openings has an axis. In some of such arrangements, the axes of the individual openings extend transverse to the longitudinal axis. For example, the plurality of openings can extend along directions orthogonal to the longitudinal axis.

The plurality of openings are spaced around the circumference of the barrel nut and can be arranged in one or more rows around the barrel nut. For example, the plurality of openings may be arranged in two or more rows. One or more rows (e.g., each row) can extend circumferentially around the barrel nut. In some preferred embodiments, one or more rows (e.g., each row) includes 20 or more openings.

The openings are, preferably, evenly spaced around the circumference of the barrel nut. Additionally, in many embodiments it may be preferred to have an even number of openings spaced around the circumference of the barrel nut such that openings are diametrically opposed in pairs. Advantageously, such an arrangement allow for pairs of openings to be presented in diametrically opposed openings in the handguard when received therein. While not limited to such, the plurality of openings of the barrel nut can be a plurality of threaded openings and the fastener can be a threaded fastener.

The fastener(s) of the disclosed embodiments can have a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut and the second end (e.g., a head) having a cross-sectional dimension greater than a cross-sectional dimension of the plate opening and/or the side opening. In some instances, the fastener may have a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut; wherein the plate opening is countersunk or counterbored to receive the second end of the fastener; and wherein the second end of the threaded fastener does not protrude beyond the plate when the system is mounted on a firearm.

In the disclosed embodiments, a width of a portion of the fastener positioned within the plate opening when the system is attached to a firearm can be at least 10% smaller, at least 20% smaller, or at least 50% smaller than a corresponding width of the plate opening so as to allow movement of the fastener from a first portion of the plate opening into a second portion of the plate opening as the handguard and/or plate rotate relative to the barrel nut.

The disclosed embodiments may have non-circular side openings of the handguard for receipt of the fastener(s) and/or plates. Additionally or alternatively, the plate openings that receive the fastener(s) may be non-circular. For example, side openings and/or plate openings may be elongated. In some embodiments, side openings and/or plate openings may be rectangular, oval, or obround, just to name a few non-limiting examples.

The present disclosure also provides systems for a firearm, comprising: a barrel nut having a circumference with a plurality of openings positioned therearound; and a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm;

wherein when mounted on the firearm, the sidewall of the handguard is captured between a head of a fastener and the barrel nut and the fastener has a portion positioned in the side opening and a portion positioned the first opening of the barrel nut; and wherein the side opening of the handguard is non-circular. The features of these systems may be combined and/or replaced with any number of features and combinations of features disclosed elsewhere.

Embodiments of the present disclosure can allow movement of the handguard relative to a barrel nut while a fastener extends through the handguard into the barrel nut. The embodiments, however, can be configured to resist rotation of the handguard relative to the barrel nut by tightening the fasteners so as to press a segment of the handguard against the barrel nut. Advantageously, disclosed arrangements can allow for further adjustment of the handguard relative to the barrel nut after the fasteners have been inserted through the handguard and into the barrel nut. This new system is believed to provide easier and, in at least some instances, better alignment of the handguard with the upper receiver of the firearm than many existing handguard attachment systems. For example, the system of the present can be arranged so as to reduce and/or avoid the use of shims.

Further forms, objects, features, aspects, benefits, advantages, and embodiments of the present invention will become apparent from a detailed description and drawings provided herewith.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded view of a handguard anchoring system, barrel portion, and upper receiver portion.

FIG. 2 is a perspective view of the system of FIG. 1.

FIG. 3 is a perspective view of the handguard anchoring system of FIG. 1.

FIG. 4 is a side view of the system of FIG. 3.

FIG. 5 is a top view of the system of FIG. 3.

FIG. 6 is an end view of a handguard, plate, and fastener assembly, with the barrel nut omitted for illustrative purposes.

FIG. 7 is an end view of the system of FIG. 3.

FIG. 8 is a side view of a portion of the handguard and barrel nut assembly, with the plate and fasteners omitted for illustrative purposes.

FIG. 9 is a side view of a barrel nut.

FIGS. 10 and 11 are perspective views of the barrel nut of FIG. 9.

FIGS. 12 and 13 are perspective views of an anchoring plate.

FIG. 14 is a side view of the plate of FIGS. 12 and 13.

FIG. 15 is a cross-sectional view of the handguard along line 15-15 of FIG. 6.

FIG. 16 is a cross-sectional view of the handguard assembly along line 16-16 of FIG. 4.

DESCRIPTION OF THE SELECTED EMBODIMENTS

For the purpose of promoting an understanding of the principles of the invention, reference will now be made to the embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Any alterations and further modifications in the described embodiments, and any further applications of the principles of the invention as described herein are contemplated as would normally occur to one

skilled in the art to which the invention relates. One embodiment of the invention is shown in great detail; although it will be apparent to those skilled in the relevant art that some features that are not relevant to the present invention may not be shown for the sake of clarity.

An exemplary handguard anchoring system 100 useful for attaching a handguard to a firearm 1000 is illustrated in the figures. The handguard anchoring system includes a handguard 102, a barrel nut 104, an anchoring plate 106, and a fastener 108. The handguard anchoring system is useful for attaching handguard 102 around a barrel 1002 that is secured to an upper receiver 1004 by the barrel nut.

The handguard has a forward end 110, a rearward end 112, and an intermediate region 114 extending between the forward and rearward ends. The rearward end of the handguard has one or more tabs 116, 118 arranged to fit alongside a portion of the upper receiver 1004 when the handguard has been system is attached to a firearm. Advantageously, once the handguard anchoring system is attached to a firearm, the one or more tabs of the handguard may aid in resisting rotation of the handguard relative to the upper receiver.

The handguard may include one or more different mounting features arranged for attaching an accessory to the firearm. For example, a first mounting feature 120 may include a rail, such as a weaver or picatinny rail, for the attachment of, for example, a flip-up front sight. A second mounting feature 122 of a different type than the first mounting feature may include a slot/hole type mounting arrangement such as an M-LOK® or MOE slot as marketed by MagPul Industries or a KeyMod slot as marketed by VLTOR Weapon Systems and Noveske Rifleworks.

At the rearward end, the handguard has a sidewall 128 with an inner surface 130 defining an internal cavity 132 arranged to receive the barrel nut. In many embodiments, the internal cavity substantially matches the shape and size of an exterior surface of the received portion of the barrel nut. For instance, the inner surface of the handguard may define a substantially round internal cavity to receive a round barrel nut.

The sidewall of the rearward end of the handguard also defines a side opening 134 that communicates with the internal cavity arranged to receive the barrel nut. FIG. 8 shows a side view of the handguard anchoring system without the plate and fasteners when the barrel nut is received in the internal cavity. As can be seen, a forward opening 140 and a rearward opening 142 in the barrel nut for receiving the fasteners are positioned within the side opening when the barrel nut is received within the handguard.

Notably, the cross-sectional dimension of the side opening in the handguard is larger than the opening(s) for receiving the fastener(s) in the barrel nut. As illustrated in FIGS. 9-11, the barrel nut has a plurality of openings positioned around the periphery thereof. In some instances, the openings in the barrel nut and the side opening in the handguard are arranged such that, regardless of the rotational position of the barrel nut inside of the handguard, at least one or more openings are completely visible through the side opening of the handguard. As will be appreciated by those of skill in the art, the openings may be threaded openings for receiving threaded fasteners.

In addition to openings for receiving the fastener(s) of the handguard anchoring system, the barrel nut can include features arranged to mate with a tool useful for securing the barrel nut to the upper receiver. For example, the barrel nut in the illustrated embodiments includes a groove 150 and notches 152 arranged to receive a barrel nut wrench. Other arrangements, however, are contemplated. For example, the

5

barrel nut may have polygonal cross-sectional shape defined by planar surfaces around the periphery arranged to cooperate with pliers or a wrench (e.g., an open-end wrench).

The barrel nut has a longitudinal axis **160** along which the barrel of the firearm is received. When positioned around a barrel, the barrel extends through aperture **162**. An internal rim **164** of the barrel nut is arranged to contact a flange of the barrel and sandwich the flange between the rim and the upper receiver when the barrel nut is secured to the upper receiver, such as with threads **166**.

The plate of the handguard anchoring system is illustrated in FIGS. **12-14**. The plate defines one or more openings **168** arranged to receive a fastener and includes a first portion **170** and a second portion **172**. The first portion has at least one outer dimension that is smaller than a corresponding outer dimension of the second portion. For example, the first portion may have a width and/or length less than the width and/or length of the second portion.

The first portion can be smaller than the corresponding side opening of the handguard such that the first portion of the plate is receivable within the side opening when the plate is positioned over the side opening. Additionally, the second portion of the plate may have at least one dimension that is larger than the side opening of the handguard such that the second portion can span a portion of the side opening and be positionable on portions of the exterior surface of the handguard on opposing sides and/or ends of the side opening.

FIG. **15** illustrates a partial cross-sectional view of the handguard and plate taken along line **15-15** of FIG. **6**. As can be seen in FIG. **15**, the first portion of the plate has a smaller width **180** than a width **182** of the side opening. Preferably, the width of first portion of the plate is sufficiently smaller than the width of the side opening so as to allow rotational adjustability of the handguard relative to the barrel nut prior to tightening of the fasteners. Once the handguard is rotationally aligned with the upper receiver (e.g., the rail of the handguard aligned with the rail of the upper receiver), the fasteners can be tightened to compress the handguard between the anchor plate and the barrel nut and, thereby, lock the handguard in position relative to the barrel nut.

The first portion of the plate also has a shorter length **184** than a length **186** of the side opening. Preferably, the length of first portion of the plate is sufficiently smaller than the length of the side opening so as to allow longitudinal adjustability of the handguard relative to the barrel nut prior to tightening of the fasteners. Accordingly, before the fasteners are tightly fastened, the first portion of the plate is capable of movement from a first section of the side opening, such as end **190**, to a second section of the side opening, such as end **192**. Advantageously, this adjustability can allow a user to adjust the spacing between the handguard and the upper receiver (e.g., move the handguard into abutting contact with the upper receiver) prior to tightening the fasteners.

When the barrel nut is positioned inside the handguard and the plate is positioned over the side opening, the sidewall of the handguard is positioned between the barrel nut and the second portion of the plate, as shown in FIG. **16**. As a fastener extending from the plate opening into the opening in the barrel nut is tightened, the fastener forces the plate against the sidewall of the handguard which, in turn, forces the handguard against the barrel nut. In this way, the handguard is securely fastened to the barrel nut.

In some embodiments, the anchoring system is arranged so that the fastener has an outer end (e.g., the head) positioned flush with or beneath the outer surface of the

6

second portion of the plate when the handguard attachments system is secured to a firearm. This can be advantageous to some users as it can reduce the possibility of an edge of the fastener catching a shooter's skin or clothing.

The handguard, barrel nut, fasteners, and/or plates described herein can be made of a variety of metals and/or polymers, including composite materials. For example, the handguard, barrel nut, fasteners, and/or plates may comprise a metal such as steel, aluminum, titanium, or magnesium, or a composite material such as carbon fiber.

In some embodiments, the handguard may comprise a first material and the plate(s) comprise a second material. For example, the handguard may comprise aluminum, magnesium, or carbon fiber and the plate(s) may comprise steel. Alternatively, the handguard may comprise magnesium or carbon fiber and the plate may comprise aluminum. It is contemplated, however, that the handguard and plates may comprise the same material, such as aluminum.

In any of the embodiments described herein the barrel nut may comprise a metal, such as steel or titanium. Barrel nuts disclosed herein may also be substantially longer than those typically found on similar firearms. For example, barrel nuts disclosed herein may have a length of more than 1 inch (e.g., 1.5 inches or more). A longer barrel nut can provide greater spacing between the openings in the barrel nut that receive the fasteners. Advantageously, this can provide greater resistance to bending of the plate and/or handguard. Moreover, a longer barrel nut can aid in the axial alignment of the handguard to the barrel.

Assemblies may include one or more plates and accompanying fasteners to secure the handguard to the barrel nut. In arrangements having more than one plate, the plates are preferably spaced from one another. For example, assemblies may have a first plate on a first side of the handguard (e.g., right side) and a second plate on a second side of the handguard (e.g., left side). Additionally or alternatively, assemblies may have plates on the top and/or bottom of the handguard.

The anchoring system can be arranged such that neither the plate nor the fasteners protrude beyond the outer surface of the handguard by more than 2 millimeters when assembled on a firearm. In some instances, an outer periphery of the plate is chamfered such that the outward facing surface of the plate, when positioned on a handguard, is free of edges defined by right angles or acute angles. Moreover, in some instance, the openings in the plate for receiving the fasteners are countersunk so the head of the fastener resides below the outermost surface of the plate. Advantageously, such arrangements can reduce the possibility of the anchoring system becoming caught on a shooter's glove, firearm sling, and/or clothing (e.g., sleeve).

The plate, fasteners, and/or barrel nut disclosed herein may be provided in a kit. For example, a kit may contain a handguard, a barrel nut, two or more plates, and/or fasteners (e.g., two fasteners per plate). Some kits may include three or more plates. Kits may also include other components such as a thread locker (e.g., thread locker sold under the name Loctite® by Henkel Corporation) and/or a paint pen or marker for an operator to use to mark the fastener and plate after tightening. Such markings can be used to indicate subsequent loosening of the fasteners.

The anchoring system may also be provided with other firearm components and/or a complete firearm. For example, an upper receiver and/or a barrel assembly for an AR-15 style pistol or rifle may be provided with a handguard and

the anchoring system disclosed herein. In some instances, the handguard anchoring system may be provided on an assembled firearm.

The following numbered clauses set out specific embodiments that may be useful in understanding the present invention:

1. A system for a firearm, comprising:
 a barrel nut having a circumference with a plurality of openings positioned therearound;
 a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm; and
 a plate defining a plate opening arranged to receive a fastener;
 wherein when mounted on the firearm, the sidewall of the handguard is captured between the plate and the barrel nut and the fastener has portions positioned in the plate opening, the side opening, and the first opening of the barrel nut.
2. The system of clause 1, wherein when the system is mounted on the firearm a width of a portion of the fastener received within the side opening of the handguard is at least 10% smaller than a corresponding width of the side opening of the handguard so as to allow movement of the fastener from a first portion of the side opening into a second portion of the side opening as the handguard rotates about an axis of the barrel nut.
3. The system of clause 1, wherein when the system is mounted on the firearm a width of a portion of the fastener received within the side opening of the handguard is at least 20% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the fastener from a first portion of the side opening into a second portion of the side opening as the handguard rotates about an axis of the barrel nut.
4. The system of clause 1, wherein when the system is mounted on the firearm a width of a portion of the fastener received within the side opening of the handguard is at least 50% smaller than a corresponding width of the side opening, so as to allow rotational movement of the handguard about the barrel nut at least about the width of the fastener before the fastener is tightly fastened for use.
5. The system of any preceding clause, wherein the plate has a first portion and a second portion, the first portion smaller than and receivable within the side opening and a second portion larger than the side opening and positionable on an exterior surface of the handguard;
 wherein the side opening of the handguard has a length and a width;
 wherein the first portion of the plate has a length and a width; and
 wherein the first portion is sufficiently smaller than the side opening of the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening when positioned therein.
6. The system of clause 5, wherein when the system is mounted on the firearm the width of the first portion of the plate is at least 10% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening as the handguard rotates about an axis of the barrel nut.
7. The system of clause 5, wherein when the system is mounted on the firearm the width of the first portion of the

plate is at least 20% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening as the handguard rotates about an axis of the barrel nut.

8. The system of any one of clause 5-7, wherein the length of the side opening is greater than the width of the side opening.

9. The system of any one of clauses 5-8, wherein the length of the first portion of the plate is greater than the width of the first portion of the plate.

10. The system of any one of clause 5-9, wherein the length of the second portion of the plate is greater than the width of the second portion of the plate.

11. The system of any one of clauses 5-10, wherein the side opening has a length and a width; and
 wherein a ratio of length:width of the first portion of the plate is greater than a ratio of length:width of the side opening.

12. The system of any preceding clause, wherein the barrel nut has a longitudinal axis along which a barrel of the firearm is received; and

wherein each opening of the plurality of openings has an axis, and the axes of the individual openings extend transverse to the longitudinal axis.

13. The system of clause 12, wherein the plurality of openings extend along directions orthogonal to the longitudinal axis.

14. The system of any preceding clause, wherein the plurality of openings are a plurality of threaded openings and the fastener is a threaded fastener.

15. The system of any preceding clause, wherein the fastener has a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut and the second end having a cross-sectional dimension greater than a cross-sectional dimension of the plate opening.

16. The system of any preceding clause, wherein the fastener has a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut;

wherein the plate opening is countersunk or counterbored to receive the second end of the fastener; and

wherein the second end of the threaded fastener does not protrude beyond the plate when the system is mounted on a firearm.

17. The system of any preceding clause, wherein a width of a portion of the fastener positioned within the plate opening when the system is attached to a firearm is at least 10% smaller than a corresponding width of the plate opening so as to allow movement of the fastener from a first portion of the plate opening into a second portion of the plate opening as the handguard and plate rotate about an axis of the barrel nut.

18. The system of any preceding clause, wherein the side opening of the handguard is non-circular.

19. The system of any preceding clause, wherein the plate opening is non-circular.

20. The system of any preceding clause, wherein the plate opening is elongated.

21. The system of any preceding clause, wherein the plate opening is rectangular, oval, or obround.

22. A system for a firearm, comprising:
 a barrel nut having a circumference with a plurality of openings positioned therearound; and
 a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining

a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm;

wherein when mounted on the firearm, the sidewall of the handguard is captured between a head of a fastener and the barrel nut and the fastener has a portion positioned in the side opening and a portion positioned the first opening of the barrel nut; and

wherein the side opening of the handguard is non-circular.

23. The system of any preceding clause, wherein the side opening is elongated.

24. The system of any preceding clause, wherein the side opening is rectangular, oval, or obround.

While the invention has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described. For example, arrangements of the handguard anchoring system may include a barrel nut and a handguard with a non-circular side opening arranged to receive a fastener passing into the barrel nut. In such arrangements, the head of the fastener may have a cross-sectional dimension that is greater than a corresponding cross-sectional dimension of the side opening such that a portion of the sidewall of the handguard is compressed between the fastener and the barrel nut when the fastener is tightened. Such an arrangement would also be configured to allow for rotational movement of the handguard relative to the barrel nut while a portion of the fastener is positioned in the side opening of the handguard.

All changes, equivalents, and modifications that come within the spirit of the inventions defined by following claims are desired to be protected. All publications, patents, and patent applications cited in this specification are herein incorporated by reference as if each individual publication, patent, or patent application were specifically and individually indicated to be incorporated by reference and set forth in its entirety herein.

The invention claimed is:

1. An assembly, comprising:

a firearm having a barrel and a barrel nut;

a handguard having a sidewall with an exterior surface and an interior surface defining an internal cavity in which at least a portion of the barrel nut of the firearm is received, the sidewall defining side openings that extend from the exterior surface to the interior surface, the side openings including a first side opening and a second side opening on a different side of the handguard than the first side opening;

a first threaded fastener having a portion positioned in the first side opening; and

a first member separating the sidewall and the portion of the first threaded fastener positioned in the first side opening;

wherein the first threaded fastener extends into the internal cavity and threadingly engages another portion of the assembly positioned between the barrel and the handguard to force the first member towards the sidewall and the sidewall towards the barrel nut of the firearm to secure the handguard to the firearm;

wherein the first and second side openings extend along a length of the barrel nut received in the handguard; and wherein the first member has a portion that is positioned outward of the exterior surface of the sidewall and is non-circular.

2. The assembly of claim 1, wherein the first side opening is non-circular.

3. The assembly of claim 2, wherein the first side opening has a closed-perimeter.

4. The assembly of claim 1, wherein the first threaded fastener has a head portion recessed within the first member.

5. The assembly of claim 1, comprising a second member having a portion positioned outward of the exterior surface of the sidewall on the different side of the handguard than the first side opening.

6. The assembly of claim 5, wherein the second member has a portion extending into the second opening and towards the internal cavity.

7. The assembly of claim 6, wherein the second member forces the sidewall towards the barrel nut of the firearm to help secure the handguard to the firearm.

8. The assembly of claim 7, wherein the second member portion positioned outward of the exterior surface of the sidewall is non-circular.

9. The assembly of claim 7, comprising a second threaded fastener having a portion positioned in the second side opening; and

wherein the second member separates the sidewall and the portion of the second fastener positioned in the second side opening.

10. The assembly of claim 9, wherein the second threaded fastener extends into the internal cavity and threadingly engages the same portion of the assembly positioned between the barrel and the handguard as the first threaded fastener to force the second member towards the sidewall.

11. The assembly of claim 10, wherein the second threaded fastener is coaxially aligned with said first threaded fastener.

12. An assembly, comprising:

a firearm having a barrel and a barrel nut;

a handguard having a sidewall with an exterior surface and an interior surface defining an internal cavity in which at least a portion of the barrel of the firearm is received, the sidewall defining side openings that extend from the exterior surface to the interior surface, the side openings including a first side opening having a closed-perimeter;

a first plate positioned over the first side opening and defining a first plate opening and a second plate opening; and

a first fastener extending through the first plate opening and having a portion positioned in the first side opening and another portion positioned in the internal cavity and a second fastener extending through the second plate opening and having a portion positioned in the first side opening and another portion positioned in the internal cavity;

wherein the first fastener and second fastener each engage another portion of the assembly positioned in the internal cavity between the barrel and the handguard to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm; and

wherein the first and second side openings are positioned along a length of the barrel nut received in the handguard.

13. The assembly of claim 12, wherein the first side opening is non-circular.

14. The assembly of claim 13, wherein the first member has a portion that is positioned outward of the exterior surface of the sidewall and is non-circular.

15. The assembly of claim 14, wherein the first member has a portion extending into the first side opening and

11

separating the sidewall and the portion of the first threaded fastener positioned in the first side opening.

16. The assembly of claim 15, wherein the first member has a portion extending into the first side opening and separating the sidewall and the portion of the second threaded fastener positioned in the first side opening.

17. The assembly of claim 14, wherein the first and second threaded fastener each has a head portion recessed within the first member.

18. The assembly of claim 17, comprising a second plate positioned over a second side opening of the side openings and on a different side of said handguard than said first opening.

19. The assembly of claim 18, wherein the second plate has a portion positioned outward of the exterior surface of the sidewall and a portion extending into the second side opening.

20. An assembly, comprising:

a firearm having a barrel and a barrel nut;

a handguard having a sidewall with an exterior surface and an interior surface defining an internal cavity in which at least a portion of the barrel nut of the firearm is received, the sidewall defining side openings that extend from the exterior surface to the interior surface, the side openings including a first side opening and a second side opening on a different side of the handguard than the first side opening;

a first threaded fastener having a portion positioned in the first side opening; and

a first member separating the sidewall and the portion of the first threaded fastener positioned in the first side opening;

wherein the first threaded fastener extends into the internal cavity and threadingly engages another portion of the assembly positioned between the barrel and the handguard to force the first member towards the sidewall and the sidewall towards the barrel nut of the firearm to secure the handguard to the firearm;

wherein the first and second side openings extend along a length of the barrel nut received in the handguard; and wherein the first side opening is non-circular.

21. The assembly of claim 20, wherein the first side opening has a closed-perimeter.

22. An assembly, comprising:

a firearm having a barrel and a barrel nut;

a handguard having a sidewall with an exterior surface and an interior surface defining an internal cavity in which at least a portion of the barrel nut of the firearm is received, the sidewall defining side openings that extend from the exterior surface to the interior surface, the side openings including a first side opening and a second side opening on a different side of the handguard than the first side opening;

a first threaded fastener having a portion positioned in the first side opening; and

a first member separating the sidewall and the portion of the first threaded fastener positioned in the first side opening; and

a second member having a portion positioned outward of the exterior surface of the sidewall on the different side of the handguard than the first side opening;

wherein the first threaded fastener extends into the internal cavity and threadingly engages another portion of

12

the assembly positioned between the barrel and the handguard to force the first member towards the sidewall and the sidewall towards the barrel nut of the firearm to secure the handguard to the firearm;

wherein the first and second side openings extend along a length of the barrel nut received in the handguard;

wherein the second member has a portion extending into the second opening and towards the internal cavity;

wherein the second member forces the sidewall towards the barrel nut of the firearm to help secure the handguard to the firearm; and

wherein the second member portion positioned outward of the exterior surface of the sidewall is non-circular.

23. An assembly, comprising:

a firearm having a barrel and a barrel nut;

a handguard having a sidewall with an exterior surface and an interior surface defining an internal cavity in which at least a portion of the barrel nut of the firearm is received, the sidewall defining side openings that extend from the exterior surface to the interior surface, the side openings including a first side opening and a second side opening on a different side of the handguard than the first side opening;

a first threaded fastener having a portion positioned in the first side opening;

a second threaded fastener having a portion positioned in the second side opening;

a first member separating the sidewall and the portion of the first threaded fastener positioned in the first side opening;

a second member having a portion positioned outward of the exterior surface of the sidewall on the different side of the handguard than the first side opening; and

wherein the first threaded fastener extends into the internal cavity and threadingly engages another portion of the assembly positioned between the barrel and the handguard to force the first member towards the sidewall and the sidewall towards the barrel nut of the firearm to secure the handguard to the firearm;

wherein the first and second side openings extend along a length of the barrel nut received in the handguard;

wherein the second member has a portion extending into the second opening and towards the internal cavity;

wherein the second member forces the sidewall towards the barrel nut of the firearm to help secure the handguard to the firearm;

wherein the second member separates the sidewall and the portion of the second fastener positioned in the second side opening; and

wherein the second threaded fastener extends into the internal cavity and threadingly engages the same portion of the assembly positioned between the barrel and the handguard as the first threaded fastener to force the second member towards the sidewall.

24. The assembly of claim 23, wherein the second threaded fastener is coaxially aligned with said first threaded fastener.