

(12) **United States Patent**
Williams

(10) **Patent No.:** **US 12,135,186 B2**
(45) **Date of Patent:** **Nov. 5, 2024**

(54) **FREE FLOATING HANDGUARD ANCHORING SYSTEM**

(71) Applicant: **Springfield, Inc.**, Geneseo, IL (US)

(72) Inventor: **Charles David Williams**, Geneseo, IL (US)

(73) Assignee: **Springfield, Inc.**, Geneseo, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/350,460**

(22) Filed: **Jul. 11, 2023**

(65) **Prior Publication Data**

US 2023/0366653 A1 Nov. 16, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/448,927, filed on Sep. 27, 2021, now Pat. No. 11,740,051, which is a continuation of application No. 16/928,136, filed on Jul. 14, 2020, now Pat. No. 11,131,525, which is a continuation of application No. 16/517,847, filed on Jul. 22, 2019, now Pat. No. 10,712,123, which is a continuation of application No. 16/003,171, filed on Jun. 8, 2018, now Pat. No. 10,401,122.

(60) Provisional application No. 62/517,133, filed on Jun. 8, 2017.

(51) **Int. Cl.**
F41C 23/16 (2006.01)
F41G 11/00 (2006.01)

(52) **U.S. Cl.**
CPC **F41C 23/16** (2013.01); **F41G 11/003** (2013.01)

(58) **Field of Classification Search**
CPC F41C 23/16
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

282,194 A	7/1883	Howe
496,231 A	4/1893	Richard et al.
541,560 A	6/1895	Lyman
802,279 A	10/1905	Frommer
861,939 A	7/1907	Benet et al.
1,065,341 A	6/1913	Browning
1,125,937 A	1/1915	Benet et al.
1,143,170 A	6/1915	Browning
1,150,756 A	8/1915	Gocke
1,266,087 A	5/1918	Williams

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2612519 A1	12/2006
CA	2616472 A1	2/2007

(Continued)

OTHER PUBLICATIONS

US 8,561,336 B2, 10/2013, Gomez (withdrawn)

(Continued)


Primary Examiner — Gabriel J. Klein

(74) Attorney, Agent, or Firm — Woodard, Emhardt, Henry, Reeves & Wagner, LLP

(57) **ABSTRACT**

Handguard anchoring systems suitable for attaching a handguard to a firearm are disclosed, including systems having a fastener that extends into a barrel nut and compresses at least a portion of the handguard between the fastener and the barrel nut. Many embodiments include openings in the handguard and/or a plate that are oversized for the fastener such that the handguard may be rotated relative to the barrel nut when a portion of the fastener is positioned within the opening.

18 Claims, 12 Drawing Sheets



US 12,135,186 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

1,474,209 A 11/1923 Reynolds
1,517,328 A 12/1924 Weiss
2,364,487 A 12/1944 Swartz
2,779,119 A 1/1957 Fawcett
2,902,933 A 9/1959 Moldofsky et al.
2,951,424 A 9/1960 Stoner
3,075,314 A 1/1963 Bakker
3,198,076 A 8/1965 Stoner
3,543,429 A 12/1970 Bendele et al.
3,721,031 A 3/1973 Falterman et al.
3,793,922 A 2/1974 Angell et al.
4,090,305 A 5/1978 Cassidy
4,304,061 A 12/1981 Brouthers
4,742,636 A 5/1988 Swan
4,765,224 A 8/1988 Morris
D300,161 S 3/1989 Baldus
4,841,657 A 6/1989 Mossberg
4,845,871 A 7/1989 Swan
5,142,806 A 9/1992 Swan
5,198,600 A 3/1993 Nama
5,225,615 A 7/1993 Talbot et al.
5,276,988 A 1/1994 Swan
5,343,650 A 9/1994 Swan
5,412,895 A 5/1995 Krieger
5,533,292 A 7/1996 Swan
5,553,329 A 7/1996 Swan
RE35,381 E 11/1996 Rose
5,590,484 A 1/1997 Mooney et al.
5,590,585 A 1/1997 Mooney
5,595,602 A 1/1997 Harlan
5,661,255 A 8/1997 Webb
5,729,927 A 3/1998 Shaver
5,740,626 A 4/1998 Schuetz et al.
5,826,363 A 10/1998 Olson
5,946,842 A 9/1999 Nyzell et al.
5,952,602 A 9/1999 Gussalli
6,044,748 A 4/2000 Westrom
6,293,040 B1 9/2001 Luth
6,295,751 B1 10/2001 Piwonski
6,321,477 B1 11/2001 Watson, Jr.
6,345,464 B1 2/2002 Kim et al.
6,418,655 B1 7/2002 Kay
6,490,822 B1 12/2002 Swan
6,499,245 B1 12/2002 Swan
6,508,027 B1 1/2003 Kim
6,606,812 B1 8/2003 Gwinn, Jr.
6,618,976 B1 9/2003 Swan
6,634,128 B1 10/2003 Vastag
6,671,990 B1 1/2004 Booth
6,694,660 B1 2/2004 Davies
6,769,209 B2 8/2004 Mendoza-Orozco
6,848,351 B1 2/2005 Davies
6,854,206 B2 2/2005 Oz
6,860,053 B2 3/2005 Christiansen
6,895,708 B2 5/2005 Kim et al.
6,959,509 B2 11/2005 Vais
7,059,076 B2 6/2006 Stoner et al.
RE39,465 E 1/2007 Swan
7,204,052 B2 4/2007 Swan
7,216,451 B1 5/2007 Troy
RE40,216 E 4/2008 Swan
7,356,962 B2 4/2008 Swan
7,363,741 B2 4/2008 DeSomma et al.
7,458,179 B2 12/2008 Swan
7,464,496 B1 12/2008 Davies et al.
7,493,721 B2 2/2009 Swan
7,523,580 B1 4/2009 Tankersley
7,584,567 B1 9/2009 DeSomma et al.
7,640,689 B2 1/2010 Fluhr
7,676,975 B2 3/2010 Phillips et al.
7,707,762 B1 5/2010 Swan
7,716,865 B2 5/2010 Daniel et al.
7,757,422 B1 7/2010 Swan
7,757,423 B1 7/2010 Swan
7,770,317 B1 8/2010 Tankersley

7,775,150 B2 8/2010 Hochstrate et al.
7,793,452 B1 9/2010 Samson et al.
7,827,722 B1 11/2010 Davies
7,905,041 B1 3/2011 Davies
D637,684 S 5/2011 Kimmel
7,941,959 B1 5/2011 Swan
7,963,203 B1 6/2011 Davies
8,028,456 B2 10/2011 Peterson
8,028,460 B2 10/2011 Williams
8,037,633 B1 10/2011 Troy
8,037,806 B2 10/2011 Davies
8,046,949 B1 11/2011 Daniel
8,051,595 B2 11/2011 Hochstrate et al.
8,069,604 B2 12/2011 LaRue
8,087,194 B1 1/2012 Vuksanovich
8,141,285 B2 3/2012 Brown
8,141,287 B2 3/2012 Dubois
8,141,289 B2 3/2012 Gomez et al.
8,201,353 B1 6/2012 Swan
8,205,373 B1 6/2012 Ubl et al.
8,230,633 B1 7/2012 Sisk
8,230,634 B1 7/2012 Davies et al.
8,234,809 B2 8/2012 Daniel
8,240,074 B2 8/2012 Vuksanovich
8,276,303 B2 10/2012 Kapusta et al.
8,276,304 B2 10/2012 Samson et al.
8,307,751 B2 11/2012 Adolphsen
8,316,574 B1 11/2012 Swan
8,336,243 B2 12/2012 Langevin et al.
8,347,540 B2 1/2013 Sirois
8,359,779 B2 1/2013 Daniel et al.
8,397,416 B2 3/2013 Laney et al.
8,429,845 B1 4/2013 Swan
8,448,367 B2 5/2013 Samson et al.
8,453,364 B2 6/2013 Kucynko
8,464,457 B2 6/2013 Troy et al.
8,468,929 B2 6/2013 Larson et al.
8,528,246 B2 9/2013 Telles
8,561,335 B2 10/2013 Brown
8,578,642 B2 11/2013 Troy et al.
8,595,970 B2 12/2013 Picciotta et al.
8,601,734 B1 12/2013 Hopkins et al.
8,607,490 B1 12/2013 Zinsner
8,806,792 B2 1/2014 Yan et al.
8,640,372 B2 2/2014 Hochstrate et al.
8,667,882 B1 3/2014 Larson et al.
8,667,883 B1 3/2014 Larson et al.
8,689,477 B2 4/2014 Gomez et al.
8,689,478 B2 4/2014 Patel
8,707,850 B1 4/2014 Davies
8,713,838 B2 5/2014 Ubl et al.
8,726,557 B2 5/2014 Stone et al.
8,726,558 B1 5/2014 Nason
8,726,559 B1 5/2014 Mueller
8,739,448 B2 6/2014 Kimmel et al.
8,739,449 B2 6/2014 Patel
8,769,853 B1 7/2014 LaRue
8,776,420 B2 7/2014 Langevin
8,782,943 B2 7/2014 Jarboe
8,783,160 B2 7/2014 Hochstrate et al.
8,806,793 B2 8/2014 Daniel et al.
8,819,980 B2 9/2014 Geissele
8,839,545 B1 9/2014 Gangl et al.
8,844,186 B2 9/2014 LeClair
RE45,185 E 10/2014 Davies
8,863,426 B1 10/2014 Zinsner
8,904,691 B1 12/2014 Kincel
8,919,025 B2 12/2014 Kucynko
8,931,196 B1 1/2015 LaRue
8,985,007 B2 3/2015 Larson et al.
8,991,092 B2 3/2015 Shipman et al.
9,003,686 B2 4/2015 Brown
9,010,009 B2 4/2015 Buxton
9,032,659 B1 5/2015 Duneman
9,140,506 B2 9/2015 Gomez
9,140,520 B2 9/2015 Lopes et al.
9,157,697 B2 10/2015 LeClair
9,200,867 B1 12/2015 Swan
9,212,865 B2 12/2015 Dubreuil

(56)

References Cited

U.S. PATENT DOCUMENTS

9,228,799	B2	1/2016	Kucynko	2013/0055613	A1	3/2013	Gomez et al.
9,234,717	B2	1/2016	Jarboe	2013/0097910	A1	4/2013	Daniel et al.
9,279,632	B2	3/2016	Hochstrate et al.	2013/0180151	A1	7/2013	Moore
9,279,638	B2	3/2016	Adair et al.	2013/0185895	A1	7/2013	Daniel et al.
9,279,639	B2	3/2016	Hines	2013/0205637	A1	8/2013	Patel
9,297,609	B2	3/2016	Burt	2013/0227869	A1	9/2013	Thordsen
9,303,949	B1	4/2016	Oglesby	2013/0263732	A1	10/2013	Kucynko
9,322,609	B2	4/2016	Davies	2014/0000142	A1	1/2014	Patel
9,335,117	B2	5/2016	Miller et al.	2014/0026459	A1	1/2014	Yan et al.
9,389,043	B1	7/2016	Zhang	2014/0033588	A1	2/2014	Laney et al.
9,453,694	B1	9/2016	Storch	2014/0033590	A1	2/2014	Gomez
9,464,864	B2	10/2016	Merlino et al.	2014/0068987	A1	3/2014	Burt
9,464,865	B2	10/2016	Shea et al.	2014/0075817	A1	3/2014	Gomez
9,476,672	B2	10/2016	Wells et al.	2014/0076146	A1	3/2014	Gomez
9,528,793	B1	12/2016	Oglesby	2014/0076147	A1	3/2014	LaRue
9,557,137	B2	1/2017	Dzwill	2014/0076148	A1	3/2014	LaRue
9,964,380	B1	5/2018	Oglesby	2014/0076152	A1	3/2014	Hochstrate et al.
10,145,648	B1	12/2018	Holder et al.	2014/0115938	A1	5/2014	Jarboe
10,345,074	B1	7/2019	Zamlinskiy	2014/0130390	A1	5/2014	Giessele
10,532,447	B2	1/2020	Hamby	2014/0144059	A1	5/2014	Giessele
11,002,509	B2	5/2021	Mayberry et al.	2014/0345179	A1	11/2014	Adair
2002/0116857	A1	8/2002	Wonisch et al.	2014/0373419	A1	12/2014	LeClair
2006/0162217	A1	7/2006	Longueira	2015/0007477	A1	1/2015	Langevin et al.
2006/0260169	A1	11/2006	Samson et al.	2015/0007478	A1	1/2015	Barrett et al.
2007/0017139	A1	1/2007	LaRue	2015/0007712	A1	1/2015	Larson et al.
2007/0033851	A1	2/2007	Hochstrate et al.	2015/0020427	A1	1/2015	Compton et al.
2007/0199435	A1	8/2007	Hochstrate et al.	2015/0135572	A1	5/2015	Davies
2007/0261285	A1	11/2007	Troy	2015/0135576	A1	5/2015	Wells et al.
2008/0092422	A1	4/2008	Daniel et al.	2015/0143730	A1	5/2015	Laney et al.
2009/0013579	A1	1/2009	Fluhr	2015/0168092	A1	6/2015	Stone
2009/0044439	A1	2/2009	Phillips et al.	2015/0168095	A1	6/2015	Dubreuil
2010/0095575	A1	4/2010	Swan	2015/0168096	A1	6/2015	Miller et al.
2010/0126054	A1	5/2010	Daniel et al.	2015/0241166	A1	8/2015	Hines
2010/0175293	A1	7/2010	Hines	2015/0247695	A1	9/2015	Jarboe
2010/0212201	A1	8/2010	Kincel et al.	2015/0247699	A1	9/2015	Davies
2010/0269392	A1	10/2010	Swan	2015/0247700	A1	9/2015	Merlino et al.
2010/0282066	A1	11/2010	Tankersley	2015/0285584	A1	10/2015	Mayberry et al.
2010/0287809	A1	11/2010	Williams	2015/0316347	A1	11/2015	Shea et al.
2010/0300277	A1	12/2010	Hochstrate et al.	2015/0369555	A1	12/2015	Daniel et al.
2010/0319231	A1	12/2010	Stone et al.	2016/0010946	A1	1/2016	Gibbens et al.
2011/0000119	A1	1/2011	Desomma et al.	2016/0033225	A1	2/2016	Selvetti
2011/0016762	A1	1/2011	Davies	2016/0054096	A1	2/2016	Dzwill
2011/0061281	A1	3/2011	Kapusta et al.	2016/0084596	A1	3/2016	Gomez
2011/0099869	A1	5/2011	Bentley	2016/0091276	A1	3/2016	Miller et al.
2011/0119981	A1	5/2011	LaRue	2016/0131447	A1	5/2016	Hochstrate et al.
2011/0126443	A1	6/2011	Sirois	2016/0153744	A1	6/2016	Teetzel et al.
2011/0167701	A1	7/2011	Williams	2016/0169617	A1	6/2016	Daley, Jr.
2011/0192066	A1	8/2011	Kimmel et al.	2016/0178316	A1	6/2016	Miller et al.
2011/0214327	A1	9/2011	DeSomma	2016/0195360	A1	7/2016	Davies
2011/0239513	A1	10/2011	Sandman	2016/0209166	A1	7/2016	Larson, Jr. et al.
2011/0247254	A1	10/2011	Barnes	2016/0223286	A1	8/2016	Storch
2011/0252625	A1	10/2011	Daniel	2016/0282069	A1	9/2016	Storch
2011/0303082	A1	12/2011	Hochstrate et al.	2016/0282083	A1	9/2016	Storch
2012/0005936	A1	1/2012	Daniel	2016/0290761	A1	10/2016	Cook, Jr. et al.
2012/0036756	A1	2/2012	Brown	2017/0059273	A1	3/2017	Geissele
2012/0042557	A1	2/2012	Gomez et al.	2017/0160048	A1	6/2017	Galletta, II
2012/0073177	A1	3/2012	Laney et al.	2018/0112952	A1	4/2018	Kincel et al.
2012/0096755	A1	4/2012	Griffin	2018/0180370	A1	6/2018	Zheng
2012/0117845	A1	5/2012	DeSomma	2018/0306551	A1	10/2018	Reid
2012/0124880	A1	5/2012	LeClair	2018/0356181	A1	12/2018	Williams
2012/0131834	A1	5/2012	Barrett et al.	2020/0240737	A1	7/2020	Wheeler et al.
2012/0131835	A1	5/2012	Barrett et al.	2023/0110575	A1	4/2023	Cinco
2012/0132068	A1	5/2012	Kucynko et al.	2023/0324141	A1	10/2023	Mansfield
2012/0137563	A1	6/2012	Ubl et al.				
2012/0180358	A1	7/2012	Samson et al.				
2012/0186123	A1	7/2012	Troy et al.				
2012/0190358	A1	7/2012	Samson				
2012/0216439	A1	8/2012	Barrett et al.				
2012/0029132	A1	11/2012	Ubl				
2012/0285317	A1	11/2012	Davies				
2012/0291329	A1	11/2012	Ubl et al.				
2012/0317859	A1	12/2012	Brown				
2012/0324775	A1	12/2012	Troy et al.				
2013/0019513	A1	1/2013	Telles				
2013/0047832	A1	2/2013	Hochstrate et al.				

FOREIGN PATENT DOCUMENTS

CA	2625261	A1	5/2007
CA	2765149	A1	12/2010
CA	2889273	A1	5/2014
CA	2877197	A1	7/2015
CZ	303 588	B6	12/2012
DE	10 2010 023 466	A1	12/2011
DE	10 2013 008 241	A1	11/2014
DE	10 2013 208 770	A1	11/2014
EP	1 998 134	A2	12/2008
EP	1 949 014	B1	1/2010
EP	2 141 441	A2	1/2010
EP	2 634 522	A1	9/2013
EP	2 446 214	B1	1/2014

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	2 191 224 B1	5/2015
EP	2 894 431 A1	7/2015
EP	2 896 927 A1	7/2015
GB	891448	3/1962
KR	10-2008-0034451	4/2008
KR	10-2008-0034454	4/2008
KR	10-2008-0036988	4/2008
KR	10-2008-0067345	7/2008
KR	10-2013-0076902	7/2013
KR	10-1358970	2/2014
KR	10-2014-0056391	5/2014
KR	10-1564570	10/2015
WO	WO 2005/047801 A3	5/2005
WO	WO 2006/103062 A1	10/2006
WO	WO 2006/103062	10/2006
WO	WO 2006/138106 A3	12/2006
WO	WO 2008/060310 A3	5/2008
WO	WO 2008/103193 A3	8/2008
WO	WO 2009/082520 A3	7/2009
WO	WO 2009/131721 A3	10/2009

WO	WO 2010/0151552	12/2010
WO	WO 2013/010515 A1	1/2013
WO	WO 2014/031593 A3	2/2014
WO	WO 2014/066759 A1	5/2014
WO	WO 2016/028908 A1	2/2016
WO	WO 2016/089863 A3	6/2016

OTHER PUBLICATIONS

Aero Precision, MrE1 Handguard Barrel Nut and AR15 Bar Barrel Nut, <https://aeroprecisionusa.com/catalogsearch/result/?q=M5E1+Handguard+Barrel+Nut>.


Daniel Defense Bolt-Up Plate, <https://danieldefense.com/catalogsearch/result/?q=bolt-up+plate>.

Noveske NSR Barrel Nut, Noveske Rifleworks, L. L. C., <https://noveske.com/products/nsr-nhr-barrel-nut/>.

Parallax Tactical, FFSSR Rail System, <https://www.firearmsinsider.tv/gun-gear-reviews/parallax-tactical-ffssr-rail>.

Seekins Precision Rail Mounting System in which a rail is attached using screws, <http://www.seekinsprecision.com/parts-and-accessories/handguards.html>.

Wilson Combat, Tactical Rail Interface (T.R.I.M.), <https://www.midwayusa.com/product/1070134354>.






Fig. 2




Fig. 3




Fig. 4






Fig. 5






Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12






Fig. 13






Fig. 16

1

FREE FLOATING HANDGUARD ANCHORING SYSTEM

BACKGROUND

The present disclosure pertains generally to firearms of various actions (e.g., bolt-action, lever-action, and semi-automatic action), including, but not limited to, modern sporting rifles like the AR-15 and M-16 style weapons. Specifically, the present disclosure pertains to systems for attaching a handguard to a firearm. Handguard anchoring systems currently exist; however, there continues to be a desire and need for new designs.

SUMMARY

The present disclosure pertains generally to systems for anchoring a handguard to a firearm. In certain aspects, the systems disclosed herein include a fastener extending through the handguard and into the barrel nut. In some instances, disclosed systems comprise a barrel nut having a circumference with a plurality of openings positioned therearound; a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm; and a plate defining a plate opening arranged to receive a fastener; wherein when mounted on the firearm, the sidewall of the handguard is captured between the plate and the barrel nut and the fastener has portions positioned in the plate opening, the side opening, and the first opening of the barrel nut.

Arrangements of the disclosed systems can have a width of a portion of the fastener received within the side opening of the handguard that is at least 10% smaller, at least 20% smaller, or at least 50% smaller than a corresponding width of the side opening of the handguard so as to allow movement of the fastener from a first portion of the side opening into a second portion of the side opening as the handguard rotates about an axis of the barrel nut. In some instances, the fastener is sufficiently smaller than the side opening so as to allow rotational movement of the handguard about the barrel nut at least about the width of the fastener, before the fastener is tightly fastened for use.

The present disclosure also provides the plate can have a first portion and a second portion, the first portion smaller than and receivable within the side opening and a second portion larger than the side opening and positionable on an exterior surface of the handguard; wherein the side opening of the handguard has a length and a width; wherein the first portion of the plate has a length and a width; and/or wherein the first portion is sufficiently smaller than the side opening of the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening when positioned therein.

The plates of the present disclosure can include a first portion having a width that is at least 10% smaller, at least 20% smaller, or at least 50% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening as the handguard rotates about an axis of the barrel nut.

In the disclosed embodiments, the length of the side opening can be greater than the width of the side opening. Additionally or alternatively, the length of the first portion of the plate can be greater than the width of the second portion of the plate so as to allow longitudinal movement of the plate

2

relative to the handguard when the fasteners are loose. Embodiments may also have the length of the second portion of the plate being greater than the width of the second portion of the plate. In some instances the ratio of length:width of the first portion of the plate is greater than a ratio of length:width of the side opening.

In the disclosed embodiments, the barrel nut can have a longitudinal axis along which a barrel of the firearm is received and each opening of the plurality of openings has an axis. In some of such arrangements, the axes of the individual openings extend transverse to the longitudinal axis. For example, the plurality of openings can extend along directions orthogonal to the longitudinal axis.

The plurality of openings are spaced around the circumference of the barrel nut and can be arranged in one or more rows around the barrel nut. For example, the plurality of openings may be arranged in two or more rows. One or more rows (e.g., each row) can extend circumferentially around the barrel nut. In some preferred embodiments, one or more rows (e.g., each row) includes 20 or more openings.

The openings are, preferably, evenly spaced around the circumference of the barrel nut. Additionally, in many embodiments it may be preferred to have an even number of openings spaced around the circumference of the barrel nut such that openings are diametrically opposed in pairs. Advantageously, such an arrangement allow for pairs of openings to be presented in diametrically opposed openings in the handguard when received therein. While not limited to such, the plurality of openings of the barrel nut can be a plurality of threaded openings and the fastener can be a threaded fastener.

The fastener(s) of the disclosed embodiments can have a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut and the second end (e.g., a head) having a cross-sectional dimension greater than a cross-sectional dimension of the plate opening and/or the side opening. In some instances, the fastener may have a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut; wherein the plate opening is countersunk or counterbored to receive the second end of the fastener; and wherein the second end of the threaded fastener does not protrude beyond the plate when the system is mounted on a firearm.

In the disclosed embodiments, a width of a portion of the fastener positioned within the plate opening when the system is attached to a firearm can be at least 10% smaller, at least 20% smaller, or at least 50% smaller than a corresponding width of the plate opening so as to allow movement of the fastener from a first portion of the plate opening into a second portion of the plate opening as the handguard and/or plate rotate relative to the barrel nut.

The disclosed embodiments may have non-circular side openings of the handguard for receipt of the fastener(s) and/or plates. Additionally or alternatively, the plate openings that receive the fastener(s) may be non-circular. For example, side openings and/or plate openings may be elongated. In some embodiments, side openings and/or plate openings may be rectangular, oval, or obround, just to name a few non-limiting examples.

The present disclosure also provides systems for a firearm, comprising: a barrel nut having a circumference with a plurality of openings positioned therearound; and a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm;

wherein when mounted on the firearm, the sidewall of the handguard is captured between a head of a fastener and the barrel nut and the fastener has a portion positioned in the side opening and a portion positioned the first opening of the barrel nut; and wherein the side opening of the handguard is non-circular. The features of these systems may be combined and/or replaced with any number of features and combinations of features disclosed elsewhere.

Embodiments of the present disclosure can allow movement of the handguard relative to a barrel nut while a fastener extends through the handguard into the barrel nut. The embodiments, however, can be configured to resist rotation of the handguard relative to the barrel nut by tightening the fasteners so as to press a segment of the handguard against the barrel nut. Advantageously, disclosed arrangements can allow for further adjustment of the handguard relative to the barrel nut after the fasteners have been inserted through the handguard and into the barrel nut. This new system is believed to provide easier and, in at least some instances, better alignment of the handguard with the upper receiver of the firearm than many existing handguard attachment systems. For example, the system of the present can be arranged so as to reduce and/or avoid the use of shims.

Further forms, objects, features, aspects, benefits, advantages, and embodiments of the present invention will become apparent from a detailed description and drawings provided herewith.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded view of a handguard anchoring system, barrel portion, and upper receiver portion.

FIG. 2 is a perspective view of the system of FIG. 1.

FIG. 3 is a perspective view of the handguard anchoring system of FIG. 1.

FIG. 4 is a side view of the system of FIG. 3.

FIG. 5 is a top view of the system of FIG. 3.

FIG. 6 is an end view of a handguard, plate, and fastener assembly, with the barrel nut omitted for illustrative purposes.

FIG. 7 is an end view of the system of FIG. 3.

FIG. 8 is a side view of a portion of the handguard and barrel nut assembly, with the plate and fasteners omitted for illustrative purposes.

FIG. 9 is a side view of a barrel nut.

FIGS. 10 and 11 are perspective views of the barrel nut of FIG. 9.

FIGS. 12 and 13 are perspective views of an anchoring plate.

FIG. 14 is a side view of the plate of FIGS. 12 and 13.

FIG. 15 is a cross-sectional view of the handguard along line 15-15 of FIG. 6.

FIG. 16 is a cross-sectional view of the handguard assembly along line 16-16 of FIG. 4.

DESCRIPTION OF THE SELECTED EMBODIMENTS

For the purpose of promoting an understanding of the principles of the invention, reference will now be made to the embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Any alterations and further modifications in the described embodiments, and any further applications of the principles of the invention as described herein are contemplated as would normally occur to one

skilled in the art to which the invention relates. One embodiment of the invention is shown in great detail; although it will be apparent to those skilled in the relevant art that some features that are not relevant to the present invention may not be shown for the sake of clarity.

An exemplary handguard anchoring system **100** useful for attaching a handguard to a firearm **1000** is illustrated in the figures. The handguard anchoring system includes a handguard **102**, a barrel nut **104**, an anchoring plate **106**, and a fastener **108**. The handguard anchoring system is useful for attaching handguard **102** around a barrel **1002** that is secured to an upper receiver **1004** by the barrel nut.

The handguard has a forward end **110**, a rearward end **112**, and an intermediate region **114** extending between the forward and rearward ends. The rearward end of the handguard has one or more tabs **116**, **118** arranged to fit alongside a portion of the upper receiver **1004** when the handguard has been system is attached to a firearm. Advantageously, once the handguard anchoring system is attached to a firearm, the one or more tabs of the handguard may aid in resisting rotation of the handguard relative to the upper receiver.

The handguard may include one or more different mounting features arranged for attaching an accessory to the firearm. For example, a first mounting feature **120** may include a rail, such as a weaver or picatinny rail, for the attachment of, for example, a flip-up front sight. A second mounting feature **122** of a different type than the first mounting feature may include a slot/hole type mounting arrangement such as an M-LOK® or MOE slot as marketed by MagPul Industries or a KeyMod slot as marketed by VLTOR Weapon Systems and Noveske Rifleworks.

At the rearward end, the handguard has a sidewall **128** with an inner surface **130** defining an internal cavity **132** arranged to receive the barrel nut. In many embodiments, the internal cavity substantially matches the shape and size of an exterior surface of the received portion of the barrel nut. For instance, the inner surface of the handguard may define a substantially round internal cavity to receive a round barrel nut.

The sidewall of the rearward end of the handguard also defines a side opening **134** that communicates with the internal cavity arranged to receive the barrel nut. FIG. 8 shows a side view of the handguard anchoring system without the plate and fasteners when the barrel nut is received in the internal cavity. As can be seen, a forward opening **140** and a rearward opening **142** in the barrel nut for receiving the fasteners are positioned within the side opening when the barrel nut is received within the handguard.

Notably, the cross-sectional dimension of the side opening in the handguard is larger than the opening(s) for receiving the fastener(s) in the barrel nut. As illustrated in FIGS. 9-11, the barrel nut has a plurality of openings positioned around the periphery thereof. In some instances, the openings in the barrel nut and the side opening in the handguard are arranged such that, regardless of the rotational position of the barrel nut inside of the handguard, at least one or more openings are completely visible through the side opening of the handguard. As will be appreciated by those of skill in the art, the openings may be threaded openings for receiving threaded fasteners.

In addition to openings for receiving the fastener(s) of the handguard anchoring system, the barrel nut can include features arranged to mate with a tool useful for securing the barrel nut to the upper receiver. For example, the barrel nut in the illustrated embodiments includes a groove **150** and notches **152** arranged to receive a barrel nut wrench. Other arrangements, however, are contemplated. For example, the

5

barrel nut may have polygonal cross-sectional shape defined by planar surfaces around the periphery arranged to cooperate with pliers or a wrench (e.g., an open-end wrench).

The barrel nut has a longitudinal axis **160** along which the barrel of the firearm is received. When positioned around a barrel, the barrel extends through aperture **162**. An internal rim **164** of the barrel nut is arranged to contact a flange of the barrel and sandwich the flange between the rim and the upper receiver when the barrel nut is secured to the upper receiver, such as with threads **166**.

The plate of the handguard anchoring system is illustrated in FIGS. **12-14**. The plate defines one or more openings **168** arranged to receive a fastener and includes a first portion **170** and a second portion **172**. The first portion has at least one outer dimension that is smaller than a corresponding outer dimension of the second portion. For example, the first portion may have a width and/or length less than the width and/or length of the second portion.

The first portion can be smaller than the corresponding side opening of the handguard such that the first portion of the plate is receivable within the side opening when the plate is positioned over the side opening. Additionally, the second portion of the plate may have at least one dimension that is larger than the side opening of the handguard such that the second portion can span a portion of the side opening and be positionable on portions of the exterior surface of the handguard on opposing sides and/or ends of the side opening.

FIG. **15** illustrates a partial cross-sectional view of the handguard and plate taken along line **15-15** of FIG. **6**. As can be seen in FIG. **15**, the first portion of the plate has a smaller width **180** than a width **182** of the side opening. Preferably, the width of first portion of the plate is sufficiently smaller than the width of the side opening so as to allow rotational adjustability of the handguard relative to the barrel nut prior to tightening of the fasteners. Once the handguard is rotationally aligned with the upper receiver (e.g., the rail of the handguard aligned with the rail of the upper receiver), the fasteners can be tightened to compress the handguard between the anchor plate and the barrel nut and, thereby, lock the handguard in position relative to the barrel nut.

The first portion of the plate also has a shorter length **184** than a length **186** of the side opening. Preferably, the length of first portion of the plate is sufficiently smaller than the length of the side opening so as to allow longitudinal adjustability of the handguard relative to the barrel nut prior to tightening of the fasteners. Accordingly, before the fasteners are tightly fastened, the first portion of the plate is capable of movement from a first section of the side opening, such as end **190**, to a second section of the side opening, such as end **192**. Advantageously, this adjustability can allow a user to adjust the spacing between the handguard and the upper receiver (e.g., move the handguard into abutting contact with the upper receiver) prior to tightening the fasteners.

When the barrel nut is positioned inside the handguard and the plate is positioned over the side opening, the sidewall of the handguard is positioned between the barrel nut and the second portion of the plate, as shown in FIG. **16**. As a fastener extending from the plate opening into the opening in the barrel nut is tightened, the fastener forces the plate against the sidewall of the handguard which, in turn, forces the handguard against the barrel nut. In this way, the handguard is securely fastened to the barrel nut.

In some embodiments, the anchoring system is arranged so that the fastener has an outer end (e.g., the head) positioned flush with or beneath the outer surface of the

6

second portion of the plate when the handguard attachments system is secured to a firearm. This can be advantageous to some users as it can reduce the possibility of an edge of the fastener catching a shooter's skin or clothing.

The handguard, barrel nut, fasteners, and/or plates described herein can be made of a variety of metals and/or polymers, including composite materials. For example, the handguard, barrel nut, fasteners, and/or plates may comprise a metal such as steel, aluminum, titanium, or magnesium, or a composite material such as carbon fiber.

In some embodiments, the handguard may comprise a first material and the plate(s) comprise a second material. For example, the handguard may comprise aluminum, magnesium, or carbon fiber and the plate(s) may comprise steel. Alternatively, the handguard may comprise magnesium or carbon fiber and the plate may comprise aluminum. It is contemplated, however, that the handguard and plates may comprise the same material, such as aluminum.

In any of the embodiments described herein the barrel nut may comprise a metal, such as steel or titanium. Barrel nuts disclosed herein may also be substantially longer than those typically found on similar firearms. For example, barrel nuts disclosed herein may have a length of more than 1 inch (e.g., 1.5 inches or more). A longer barrel nut can provide greater spacing between the openings in the barrel nut that receive the fasteners. Advantageously, this can provide greater resistance to bending of the plate and/or handguard. Moreover, a longer barrel nut can aid in the axial alignment of the handguard to the barrel.

Assemblies may include one or more plates and accompanying fasteners to secure the handguard to the barrel nut. In arrangements having more than one plate, the plates are preferably spaced from one another. For example, assemblies may have a first plate on a first side of the handguard (e.g., right side) and a second plate on a second side of the handguard (e.g., left side). Additionally or alternatively, assemblies may have plates on the top and/or bottom of the handguard.

The anchoring system can be arranged such that neither the plate nor the fasteners protrude beyond the outer surface of the handguard by more than 2 millimeters when assembled on a firearm. In some instances, an outer periphery of the plate is chamfered such that the outward facing surface of the plate, when positioned on a handguard, is free of edges defined by right angles or acute angles. Moreover, in some instance, the openings in the plate for receiving the fasteners are countersunk so the head of the fastener resides below the outermost surface of the plate. Advantageously, such arrangements can reduce the possibility of the anchoring system becoming caught on a shooter's glove, firearm sling, and/or clothing (e.g., sleeve).

The plate, fasteners, and/or barrel nut disclosed herein may be provided in a kit. For example, a kit may contain a handguard, a barrel nut, two or more plates, and/or fasteners (e.g., two fasteners per plate). Some kits may include three or more plates. Kits may also include other components such as a thread locker (e.g., thread locker sold under the name Loctite® by Henkel Corporation) and/or a paint pen or marker for an operator to use to mark the fastener and plate after tightening. Such markings can be used to indicate subsequent loosening of the fasteners.

The anchoring system may also be provided with other firearm components and/or a complete firearm. For example, an upper receiver and/or a barrel assembly for an AR-15 style pistol or rifle may be provided with a handguard and

the anchoring system disclosed herein. In some instances, the handguard anchoring system may be provided on an assembled firearm.

The following numbered clauses set out specific embodiments that may be useful in understanding the present invention:

1. A system for a firearm, comprising:
 a barrel nut having a circumference with a plurality of openings positioned therearound;
 a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm; and
 a plate defining a plate opening arranged to receive a fastener;
 wherein when mounted on the firearm, the sidewall of the handguard is captured between the plate and the barrel nut and the fastener has portions positioned in the plate opening, the side opening, and the first opening of the barrel nut.
2. The system of clause 1, wherein when the system is mounted on the firearm a width of a portion of the fastener received within the side opening of the handguard is at least 10% smaller than a corresponding width of the side opening of the handguard so as to allow movement of the fastener from a first portion of the side opening into a second portion of the side opening as the handguard rotates about an axis of the barrel nut.
3. The system of clause 1, wherein when the system is mounted on the firearm a width of a portion of the fastener received within the side opening of the handguard is at least 20% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the fastener from a first portion of the side opening into a second portion of the side opening as the handguard rotates about an axis of the barrel nut.
4. The system of clause 1, wherein when the system is mounted on the firearm a width of a portion of the fastener received within the side opening of the handguard is at least 50% smaller than a corresponding width of the side opening, so as to allow rotational movement of the handguard about the barrel nut at least about the width of the fastener before the fastener is tightly fastened for use.
5. The system of any preceding clause, wherein the plate has a first portion and a second portion, the first portion smaller than and receivable within the side opening and a second portion larger than the side opening and positionable on an exterior surface of the handguard;
 wherein the side opening of the handguard has a length and a width;
 wherein the first portion of the plate has a length and a width; and
 wherein the first portion is sufficiently smaller than the side opening of the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening when positioned therein.
6. The system of clause 5, wherein when the system is mounted on the firearm the width of the first portion of the plate is at least 10% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening as the handguard rotates about an axis of the barrel nut.
7. The system of clause 5, wherein when the system is mounted on the firearm the width of the first portion of the

plate is at least 20% smaller than a corresponding width of the side opening in the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening as the handguard rotates about an axis of the barrel nut.

8. The system of any one of clause 5-7, wherein the length of the side opening is greater than the width of the side opening.

9. The system of any one of clauses 5-8, wherein the length of the first portion of the plate is greater than the width of the first portion of the plate.

10. The system of any one of clause 5-9, wherein the length of the second portion of the plate is greater than the width of the second portion of the plate.

11. The system of any one of clauses 5-10, wherein the side opening has a length and a width; and
 wherein a ratio of length:width of the first portion of the plate is greater than a ratio of length:width of the side opening.

12. The system of any preceding clause, wherein the barrel nut has a longitudinal axis along which a barrel of the firearm is received; and

wherein each opening of the plurality of openings has an axis, and the axes of the individual openings extend transverse to the longitudinal axis.

13. The system of clause 12, wherein the plurality of openings extend along directions orthogonal to the longitudinal axis.

14. The system of any preceding clause, wherein the plurality of openings are a plurality of threaded openings and the fastener is a threaded fastener.

15. The system of any preceding clause, wherein the fastener has a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut and the second end having a cross-sectional dimension greater than a cross-sectional dimension of the plate opening.

16. The system of any preceding clause, wherein the fastener has a first end and a second end, the first end positionable in the at least one of the plurality of openings in the barrel nut;

wherein the plate opening is countersunk or counterbored to receive the second end of the fastener; and

wherein the second end of the threaded fastener does not protrude beyond the plate when the system is mounted on a firearm.

17. The system of any preceding clause, wherein a width of a portion of the fastener positioned within the plate opening when the system is attached to a firearm is at least 10% smaller than a corresponding width of the plate opening so as to allow movement of the fastener from a first portion of the plate opening into a second portion of the plate opening as the handguard and plate rotate about an axis of the barrel nut.

18. The system of any preceding clause, wherein the side opening of the handguard is non-circular.

19. The system of any preceding clause, wherein the plate opening is non-circular.

20. The system of any preceding clause, wherein the plate opening is elongated.

21. The system of any preceding clause, wherein the plate opening is rectangular, oval, or obround.

22. A system for a firearm, comprising:

a barrel nut having a circumference with a plurality of openings positioned therearound; and

a handguard having a sidewall defining an internal cavity arranged to receive the barrel nut, the sidewall defining

9

a side opening that exposes a first opening of the plurality of openings when the barrel nut and the handguard are mounted on the firearm;

wherein when mounted on the firearm, the sidewall of the handguard is captured between a head of a fastener and the barrel nut and the fastener has a portion positioned in the side opening and a portion positioned the first opening of the barrel nut; and wherein the side opening of the handguard is non-circular.

23. The system of any preceding clause, wherein the side opening is elongated.

24. The system of any preceding clause, wherein the side opening is rectangular, oval, or obround.

While the invention has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only the preferred embodiment has been shown and described. For example, arrangements of the handguard anchoring system may include a barrel nut and a handguard with a non-circular side opening arranged to receive a fastener passing into the barrel nut. In such arrangements, the head of the fastener may have a cross-sectional dimension that is greater than a corresponding cross-sectional dimension of the side opening such that a portion of the sidewall of the handguard is compressed between the fastener and the barrel nut when the fastener is tightened. Such an arrangement would also be configured to allow for rotational movement of the handguard relative to the barrel nut while a portion of the fastener is positioned in the side opening of the handguard.

All changes, equivalents, and modifications that come within the spirit of the inventions defined by following claims are desired to be protected. All publications, patents, and patent applications cited in this specification are herein incorporated by reference as if each individual publication, patent, or patent application were specifically and individually indicated to be incorporated by reference and set forth in its entirety herein.

The invention claimed is:

1. An assembly comprising:

a firearm having a barrel and a barrel nut;
a handguard having a sidewall defining an internal cavity arranged to receive the barrel and the barrel nut, the sidewall defining a first side opening that exposes at least a portion of the barrel nut when the barrel nut and the handguard are mounted on the firearm, wherein a length of the first side opening is greater than a width of the first side opening;

a first plate positioned over the first side opening, wherein the first plate defines a first plate opening arranged to receive a first fastener and a second plate opening arranged to receive a second fastener;

a second side opening defined through the sidewall, wherein the second side opening exposes at least a portion of the barrel nut when the barrel nut and the handguard are mounted on the firearm, and wherein a length of the second side opening is greater than a width of the second side opening;

a second plate positioned over the second side opening, wherein the second plate defines a third plate opening arranged to receive a third fastener;

wherein the first fastener has a first end and a second end, and wherein the first fastener first end engages another portion of the assembly positioned in the internal cavity between the barrel and the handguard to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm;

10

wherein the first plate opening is countersunk or counterbored to receive the first fastener second end;

wherein the first fastener second end does not protrude beyond the first plate when the system is mounted on the firearm; and

wherein the third fastener has a first end and a second end, and wherein the third fastener first end engages another portion of the assembly positioned in the internal cavity between the barrel and the handguard to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm.

2. The system of claim 1, wherein the first plate has a first portion and a second portion, the first portion smaller than and receivable within the first side opening and the second portion larger than the first side opening and positionable on an exterior surface of the handguard.

3. The system of claim 2,

wherein the first portion of the plate has a length and a width; and

wherein the first portion is sufficiently smaller than the side opening of the handguard so as to allow movement of the first portion of the plate from a first section of the side opening into a second section of the side opening when positioned therein.

4. The system of claim 1, wherein the second fastener has a first end and a second end, and wherein the second fastener first end engages another portion of the assembly positioned in the internal cavity between the barrel and the handguard to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm.

5. The system of claim 4, wherein the second plate opening is countersunk or counterbored to receive the second fastener second end; and

wherein the second fastener second end does not protrude beyond the first plate when the system is mounted on the firearm.

6. The system of claim 1, wherein the third plate opening is countersunk or counterbored to receive the third fastener second end; and

wherein the third fastener second end does not protrude beyond the second plate when the system is mounted on the firearm.

7. The system of claim 1, wherein the second plate has a first portion and a second portion, the first portion smaller than and receivable within the second side opening and the second portion larger than the second side opening and positionable on an exterior surface of the handguard.

8. The system of claim 1,

wherein the second plate defines a fourth plate opening arranged to receive a fourth fastener; and

wherein the fourth fastener has a first end and a second end, and wherein the fourth fastener first end engages another portion of the assembly positioned in the internal cavity between the barrel and the handguard to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm.

9. The system of claim 1, wherein the barrel nut includes a circumference with a plurality of openings positioned therearound.

10. The system of claim 9, wherein the first fastener engages a first opening of the plurality of openings positioned around the circumference of the barrel nut to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm.

11. The system of claim 10, wherein the first plate has a first portion and a second portion, the first portion smaller

11

than and receivable within the first side opening and the second portion larger than the first side opening and positionable on an exterior surface of the handguard.

12. The system of claim 10, wherein the first plate defines a second plate opening arranged to receive a second fastener. 5

13. The system of claim 12, wherein the second fastener has a first end and a second end, and wherein the second fastener engages a second opening of the plurality of openings positioned around the circumference of the barrel nut to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm. 10

14. The system of claim 13, wherein the second plate opening is countersunk or counterbored to receive the second fastener second end; and 15

wherein the second fastener second end does not protrude beyond the first plate when the system is mounted on the firearm.

15. The system of claim 14, further comprising:

a second side opening defined through the sidewall, wherein the second side opening exposes at least a portion of the barrel nut when the barrel nut and the handguard are mounted on the firearm, and wherein a length of the second side opening is greater than a width of the second side opening; 20

a second plate positioned over the second side opening, wherein the second plate defines a third plate opening arranged to receive a third fastener; and 25

12

wherein the third fastener has a first end and a second end, and wherein the third fastener engages a third opening of the plurality of openings positioned around the circumference of the barrel nut to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm.

16. The system of claim 15, wherein the third plate opening is countersunk or counterbored to receive the third fastener second end; and wherein the third fastener second end does not protrude beyond the second plate when the system is mounted on the firearm.

17. The system of claim 16, wherein the second plate defines a fourth plate opening arranged to receive a fourth fastener; and

wherein the fourth fastener has a first end and a second end, and wherein the fourth fastener engages a fourth opening of the plurality of openings positioned around the circumference of the barrel nut to force the sidewall of the handguard towards the barrel nut of the firearm to secure the handguard to the firearm.

18. The system of claim 17, wherein the fourth plate opening is countersunk or counterbored to receive the fourth fastener second end; and wherein the fourth fastener second end does not protrude beyond the second plate when the system is mounted on the firearm.

* * * * *